

Stormwater Checklist for Small Projects

Municipal Regional Stormwater Permit (MRP 3.0)

Complete this form for smaller detached single-family home projects that are not part of a larger plan of development and create and/or replace less than 10,000 square feet of impervious surface; or for all other types of projects that create and/or replace 2,500 square feet or more and less than 5,000 square feet of impervious surface.

For larger detached single-family home projects that create and/or replace 10,000 square feet of impervious surface and other projects that create and/or replace 5,000 square feet or more of impervious surface, use the C.3-C.6 Development Review Checklist.

A. F	Projec	ct Inf	ormation		
	A.1	A.1 Project Name:			
	A.2	Proj	ect Address:		
	A.3	Proj	ect APN:		
В.	Selec	t Ap	propriate Site I	Design Mea	sures
	B.1 [oes	the project crea	te and/or rep	olace 2,500 square feet or more of impervious surface? ☐ Yes ☐ No
		>	regarding site of	design meas	ude at least one of the Site Design Measures listed below in section a through f. ¹ Fact sheets cures a through f may be downloaded on the <u>New Development page</u> of the Flowstobay tobay.org/preventing-stormwater-pollution/with-new-redevelopment/c-3-regulated-projects)
			may be require	d at municip	shall be encouraged to implement appropriate site design measures from the list below, which ality discretion. Consult with municipal staff about requirements for your project.
	B.2 C	On th	e list below, indi	cate whethe	r each site design measure is included in the project plans and the plan sheet number:
		Yes	No No	Plan Sheet No.	Site Design Measure
					Direct roof runoff into cisterns or rain barrels and use rainwater for irrigation or other non-potable use.
					b. Direct roof runoff onto vegetated areas.
					c. Direct runoff from sidewalks, walkways, and/or patios onto vegetated areas.
					d. Direct runoff from driveways and/or uncovered parking lots onto vegetated areas.
					e. Construct sidewalks, walkways, and/or patios with permeable surfaces.
					f. Construct bike lanes, driveways, and/or uncovered parking lots with permeable surfaces.
					g. Minimize land disturbance and impervious surface (especially parking lots).
					h. Maximize permeability by clustering development and preserving open space.
					i. Use micro-detention, including distributed landscape-based detention.
					j. Protect sensitive areas, including wetland and riparian areas, and minimize changes to the natural topography.
					k. Self-treating area (see Section 4.1 of the C.3 Regulated Projects Guide)
					I. Self-retaining area (see Section 4.2 of the C.3 Regulated Projects Guide)

1

Last modified 7/1/23

¹ See MRP Provision C.3.i.i

C. Select appropriate source controls (Encouraged for all projects; may be required at municipal discretion. Consult municipal staff.)

Are these features in project?		Features that require source controls	Source control measures ² (Refer to Local Source Control List for detailed requirements)		Is source control measure included in project plans?		
Yes	No			Yes	No	Plan Sheet No.	
		Storm Drain	 Mark on-site inlets with the words "No Dumping! Flows to Bay" or equivalent. 				
		Floor Drains	 Plumb interior floor drains to sanitary sewer³ [or prohibit]. 				
		Parking garage	 Plumb interior parking garage floor drains to sanitary sewer.⁴ 				
		Landscaping	 Retain existing vegetation as practicable & consider regenerative practices.⁴ Select diverse species appropriate to the site. Include plants that are pest-and/or disease-resistant, drought-tolerant, and/or attract beneficial insects. Use Integrated Pest Management (i.e., minimize pesticide & fertilizer use.) Use efficient irrigation system; design to minimize runoff. 				
		Pool/Spa/Fountain	 Provide connection to the sanitary sewer to facilitate draining.⁴ 				
		Food Service Equipment (non- residential)	Provide a sink or other area for equipment cleaning, which is: Connected to a grease interceptor prior to sanitary sewer discharge. Large enough for the largest mat or piece of equipment to be cleaned. Indoors or in an outdoor roofed area designed to prevent stormwater run-on and run-off, and signed to require equipment washing in this area.				
		Refuse Areas	 Provide a roofed and enclosed area for dumpsters, recycling containers, etc., designed to prevent stormwater run-on and runoff. Connect any drains in or beneath dumpsters, compactors, and tallow bin areas serving food service facilities to the sanitary sewer.⁴ 				
		Outdoor Process Activities ⁵	 Perform process activities either indoors or in roofed outdoor area, designed to prevent stormwater run-on and runoff, and to drain to the sanitary sewer.⁴ 				
		Outdoor Equipment/ Materials Storage	 Cover the area or design to avoid pollutant contact with stormwater runoff. Locate area only on paved and contained areas. Roof storage areas that will contain non-hazardous liquids, drain to sanitary sewer³, and contain by berms or similar. 				
		Vehicle/ Equipment Cleaning	 Roof, pave and berm wash area to prevent stormwater run-on and runoff, plumb to the sanitary sewer⁴, and sign as a designated wash area. Commercial car wash facilities shall discharge to the sanitary sewer.⁴ 				
		Vehicle/ Equipment Repair and Maintenance	 Designate repair/maintenance area indoors, or an outdoors area designed to prevent stormwater run-on and runoff and provide secondary containment. Do not install drains in the secondary containment areas. No floor drains unless pretreated prior to discharge to the sanitary sewer.⁴ Connect containers or sinks used for parts cleaning to the sanitary sewer.⁴ 				
		Fuel Dispensing Areas	 Fueling areas shall have impermeable surface that is a) minimally graded to prevent ponding and b) separated from the rest of the site by a grade break. Canopy shall extend at least 10 ft. in each direction from each pump and drain away from fueling area. 				
		Loading Docks	 Cover and/or grade to minimize run-on to and runoff from the loading area. Position downspouts to direct stormwater away from the loading area. Drain water from covered/roofed loading dock areas to the sanitary sewer.⁴ Install door skirts between the trailers and the building. 				
		Fire Sprinklers	 Design for discharge of fire sprinkler test water to landscape or sanitary sewer⁴ 				
		Miscellaneous Drain or Wash Water	 Drain condensate of air conditioning units to landscaping. Large air conditioning units may connect to the sanitary sewer.⁴ Roof drains shall drain to unpaved areas where practicable. Drain boiler drain lines, roof top equipment, all washwater to sanitary sewer⁴. 				
		Architectural Copper	 Drain rinse water to landscaping, discharge to sanitary sewer⁴, or collect and dispose properly offsite. See flyer "Requirements for Architectural Copper." 				

² See MRP Provision C.3.a.i.(7).

³ Any connection to the sanitary sewer system is subject to sanitary district approval.

⁴ See the regenerative landscaping principles and practices developed by ReScape California (formerly Bay-Friendly) at www.rescapeca.org

⁵ Businesses that may have outdoor process activities/equipment include machine shops, auto repair, industries with pretreatment facilities.

D. Implem	ent co	onstruction Best Management Practices (BMPs) (Required for all projects.)						
D.1								
D.2 A	All proj	ects require appropriate stormwater BMPs during construction - indicate which BMPs are included in the project, below.						
Yes	No	Best Management Practice (BMP)						
		Attach the San Mateo Countywide Water Pollution Prevention Program's construction BMP plan sheet to project plans and require contractor to implement the applicable BMPs on the plan sheet. ⁶						
		Temporary erosion controls to stabilize all denuded areas until permanent erosion controls are established.						
		Delineate with field markers the following areas: clearing limits, easements, setbacks, sensitive or critical areas, buffer zones, trees to be protected and retained, and drainage courses.						
		 Provide notes, specifications, or attachments describing the following: Construction, operation and maintenance of erosion and sediment controls, include inspection frequency; Methods and schedule for grading, excavation, filling, clearing of vegetation, and storage and disposal of excavated or cleared material; Specifications for vegetative cover & mulch, include methods and schedules for planting and fertilization; Provisions for temporary and/or permanent irrigation. 						
		Perform clearing and earth moving activities only during dry weather.						
		Use sediment controls or filtration to remove sediment when dewatering and obtain all necessary permits.						
		Protect all stormdrain inlets in vicinity of site using sediment controls (e.g., berms, socks, fiber rolls, or filters.)						
		Trap sediment on-site, using BMPs such as sediment basins or traps, earthen dikes or berms, silt fences, check dams, compost blankets or jute mats, covers for soil stockpiles, etc.						
		Divert on-site runoff around exposed areas; divert off-site runoff around the site (e.g., swales and dikes).						
		Protect adjacent properties and undisturbed areas from construction impacts using vegetative buffer strips, sediment barriers or filters, dikes, mulching, or other measures as appropriate.						
		Limit construction access routes and stabilize designated access points.						
	□ No cleaning, fueling, or maintaining vehicles on-site, except in a designated area where washwater is contained and treated.							
		Store, handle, and dispose of construction materials/wastes properly to prevent contact with stormwater.						
		Contractor shall train and provide instruction to all employees/subcontractors re: construction BMPs.						
		Control and prevent the discharge of all potential pollutants, including pavement cutting wastes, paints, concrete, petroleum products, chemicals, washwater or sediments, rinse water from architectural copper, and non-stormwater discharges to storm drains and watercourses.						
Name	of app	olicant completing the form:						
		Signature: Date:						
E. Comm	ents (1	for municipal staff use only):						
	-	nunicipal staff use only): otes:						
		otes:						
		otes:						

Section D Notes:

 $^{^{\}rm 6}$ Ask municipal staff for the SMCWPPP Construction BMP Plan Sheet.